

SAMSUNG

A Good Air Conditioning Solution
for Your Space



اسپلیت کاستی چهار طرفه
4 Way Cassette Type





• صرفه جویی در مصرف انرژی تا ۶۰٪ (در مدل های اینورتر)

• جریان هوای فراگیر در همه فضا

• امکان تغییر سرعت پرتاب باد برای سقف های بلند

• متر اژ لوله کشی طولانی جهت ساختمان های بلند

• قابلیت کارکرد تا دمای ۵۴ درجه سانتی گراد

• مجهز به پمپ تخلیه آب قدرتمند

• قابلیت تزریق هوای تازه ورودی

• دارای مدل های سرمایشی/سرمایشی و گرمایشی

• مجهز به فیلتر قابل شستشو



دستگاه کاستی چهار طرفه سامسونگ با طراحی مدرن و زیبا سبب توزیع یکنواخت هوا در محیط شده و به جذابیت فضای شما می افزاید. این دستگاه مجهز به پمپ تخلیه آب قدرتمند بوده و با قابلیت نصب و کاربری آسان مناسب برای فضاهای اداری و تجاری می باشد.



Model Name	Indoor Unit			NS0184HREB/HAC	NS0244HREB/HAC	NS0364HREB/HAC	NS0364HREB/HAC	NS0484HREB/HAC
	Outdoor Unit			RC018FQREB/HAC	RC024FQREB/HAC	RC036FQREB/HAC	RC036FQRGB/HAC	RC048FQRGB/HAC
Mode				Heat Pump	Heat Pump	Heat Pump	Heat Pump	Heat Pump
Performance	Capacity(Nominal)	Cooling	Btu/h	18,500	24,000	36,000	36,000	48,000
		Heating	Btu/h	21,500	26,000	36,000	36,000	50,000
Power	Power Input (Nominal)	Cooling	kW	2.12	2.70	3.70	3.70	5.40
		Heating	kW	2.00	2.55	3.45	3.20	5.39
	Current Input (Nominal)	Cooling	A	9.5	11.5	15.2	6.2	9.5
		Circuit Breaker	A	20	20	30	20	20
Piping Connections	Liquid Pipe		Φ, mm (inch)	6.35 (1/4)	6.35 (1/4)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)
		Gas Pipe	Φ, mm (inch)	12.70 (1/2)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)	19.05 (3/4)
	Installation Limitation	Max. Length	m	30.0	30.0	50.0	50.0	50.0
		Max. Height	m	15.0	15.0	30.0	30.0	30.0
Refrigerant	Type			R22	R22	R22	R22	R22
INDOOR UNIT								
Power Supply			Φ, #, V, Hz	1, 2, 220-240, 50	1, 2, 220-240, 50	1, 2, 220-240, 50	1, 2, 220-240, 50	1, 2, 220-240, 50
Fan	Air Flow Rate	High / Mid / Low	CMM	-	-	26.2 / 25.2 / 24.5	26.2 / 25.2 / 24.5	41.13 / 37.65 / 33.95
Drain	Drain Pipe		Φ, mm	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)
Sound	Sound Pressure	High / Low	dB(A)	35 / 34	42 / 41	43 / 43	43 / 43	47 / 47
External Dimension	Net Weight		kg	24.0	24.0	30.0	30.0	30.5
	Net Dimensions		mm	840 x 218 x 840	840 x 218 x 840	840 x 298 x 840	840 x 298 x 840	840 x 298 x 840
Panel Size	Panel model			P4SMA	P4SMA	P4SMA	P4SMA	P4SMA
	Panel Net Weight		kg	7.0	7.0	7.0	7.0	7.0
	Net Dimensions		mm	950 x 45 x 950	950 x 45 x 950	950 x 45 x 950	950 x 45 x 950	950 x 45 x 950
Additional Accessories	Drain pump	Drain pump		Built-in	Built-in	Built-in	Built-in	Built-in
		Max. lifting Height / Displacement	mm / liter/h	750 / 24	750 / 24	750 / 24	750 / 24	750 / 24
	Air Filter			Long life filter	Long life filter	Long life filter	Long life filter	Long life filter
OUTDOOR UNIT								
Power Supply			Φ, #, V, Hz	1, 2, 220-240, 50	1, 2, 220-240, 50	1, 2, 220-240, 50	3, 4, 380-415, 50	3, 4, 380-415, 50
Sound	Sound Pressure		dB(A)	51 / 52	54 / 55	53 / 55	54 / 56	55 / 57
External Dimension	Net Weight		kg	41	55	85	85	104
	Net Dimensions (WxHxD)		mm	790 x 548 x 285	880 x 638 x 310	881 x 931 x 320	881 x 931 x 320	932 x 1,128 x 375
Operating Temp. Range	Cooling		°C	21 ~ 54	21 ~ 54	21 ~ 54	21 ~ 54	21 ~ 54
	Heating		°C	-5 ~ 24	-5 ~ 24	-5 ~ 24	-5 ~ 24	-5 ~ 24

Email:sac@sampakhsh.com تلفن دفتر فروش: ۰۲۱-۷۳۰۷۵۵۵۵

Optional Accessories





Model Name	Indoor Unit			NS0714DXEA	NS0904DXEA	NS1254DXEA	NS1404DXEA
	Outdoor Unit			RC071DHXEA	RC090DHXEA	RC125DHXGA	RC140DHXGA
Mode				Heat Pump	Heat Pump	Heat Pump	Heat Pump
Performance	Capacity (Nominal)	Cooling	Btu/h	7,500 / 24,200 / 27,300	10,200 / 30,700 / 34,100	11,900 / 42,700 / 47,800	11,900 / 47,800 / 52,900
		Heating	Btu/h	6,500 / 27,300 / 30,700	7,500 / 34,100 / 47,400	10,200 / 47,800 / 55,300	11,900 / 54,600 / 61,400
	Energy Grade (C) / (H)			A / A	A / A	A / A	A / A
Power	Power Input (Nominal)	Cooling	kW	0.35 / 2.21 / 4.00	0.6 / 2.8 / 3.7	0.8 / 3.89 / 4.5	0.8 / 4.36 / 5.4
		Heating	kW	0.35 / 2.22 / 4.00	0.46 / 2.77 / 5.2	0.81 / 3.88 / 4.88	0.7 / 4.43 / 6.16
	Current Input (Nominal)	Cooling	A	2.0 / 10.5 / 12.0	3.0 / 12.5 / 18.7	2.1 / 6.1 / 12.1	2.1 / 7.5 / 12.0
		Heating	A	2.0 / 10.5 / 12.0	2.5 / 12.2 / 22.7	2.1 / 6.1 / 16.1	2.1 / 7.4 / 16.1
	Circuit Breaker (MCCB+ELB / ELCB)			25	30	20	20
COP	Nominal Cooling			3.21	3.21	3.21	3.21
	Nominal Heating			3.62	3.61	3.61	3.61
Piping Connections	Liquid Pipe	Φ, mm (inch)		6.35 (1/4)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)
	Gas Pipe	Φ, mm (inch)		15.88 (5/8)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)
	Installation Limitation	Max. Length	m	50	50	75	75
		Max. Height	m	30	30	30	30
Refrigerant	Type			R410A	R410A	R410A	R410A
INDOOR UNIT							
Power Supply			Φ, #, V, Hz	1, 2, 220-240, 50	1, 2, 220-240, 50	1, 2, 220-240, 50	1, 2, 220-240, 50
Fan	Air Flow Rate	High / Mid / Low	CMM	19.5 / 16.5 / 14.5	24.5 / 21.0 / 17.5	30.0 / 24.0 / 19.0	30.0 / 25.5 / 20.5
	External Static Pressure	Min. / Std. / Max.	mmAq	-	-	-	-
Drain	Drain Pipe	Φ, mm		VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)	VP25 (OD 32, ID 25)
Sound	Sound Pressure	High / Mid / Low	dB(A)	36 / 32 / 28	40 / 36 / 32	44 / 40 / 36	45 / 41.5 / 38
External Dimension	Weight	kg		15	17	19	21
	Net Dimensions (WxHxD)	mm		840 x 204 x 840	840 x 246 x 840	840 x 288 x 840	840 x 288 x 840
Panel Size	Panel Net Weight	kg		5.9	5.9	5.9	5.9
	Net Dimensions (WxHxD)	mm		950 x 45 x 950	950 x 45 x 950	950 x 45 x 950	950 x 45 x 950
Additional Accessories	Drain pump	Drain pump	-	Built-in	Built-in	Built-in	Built-in
		Max. lifting Height / Displacement	mm / liter/h	750 / 24	750 / 24	750 / 24	750 / 24
	Air Filter			Long life filter	Long life filter	Long life filter	Long life filter
OUTDOOR UNIT							
Power Supply			Φ, #, V, Hz	1, 2, 220-240, 50	1, 2, 220-240, 50	3, 4, 380-415, 50	3, 4, 380-415, 50
Sound	Sound Pressure	dB(A)		49 / 51	51 / 52	51 / 52	52 / 54
External Dimension	Net Weight	kg		55	72	91	91
	Net Dimensions (WxHxD)	mm		880 x 798 x 310	940 x 998 x 330	940 x 1,210 x 330	940 x 1,210 x 330
Operating Temp. Range	Cooling	°C		-15 ~ 50	-15 ~ 50	-15 ~ 50	-15 ~ 50
	Heating	°C		-20 ~ 24	-20 ~ 24	-20 ~ 24	-20 ~ 24

Email: sac@sampakhsh.com | تلفن دفتر فروش: ۰۲۱-۷۳۰۷۵۵۵۵


Optional Accessories

Individual Controllers



MR-EH00

Panel



PC4NUSKE